



**SHEET NOTES**

1. EXISTING HOLLOW METAL DOOR
2. EXISTING CONCRETE WALL PANEL
3. EXISTING OVERHEAD DOOR, TYPICAL
4. EXISTING EDGE OF DOCK DOCK BOARD
5. EXISTING METAL STAIRS
6. EXISTING 2-HOUR RATED TENANT WALL
7. EXISTING FIRE RISER ROOM
8. EXISTING PIPE BOLLARDS TO REMAIN
9. EXISTING OPENINGS IN EXISTING TENANT WALL TO BE IN-FILLED TO MATCH UL ASSEMBLY RATING OF 2-HOURS, U-419
10. EXISTING A.D.A. PARKING & ACCESSIBLE ROUTE
11. EXISTING "APPLIED" TILT WALL PANEL
12. EXISTING ELECTRICAL SERVICE
13. NEW DARK BRONZE WITH GRAY GLASS ALUMINUM STOREFRONT WINDOWS AND DOORS. SAW CUT CONCRETE WALL PANELS TO ACCOMMODATE INSTALLATION OF NEW WINDOW FRAMES
14. A.D.A. DRINKING FOUNTAIN
15. WALL MOUNTED SERVICE SINK
16. NOT USED
17. NOT USED
18. NEW CONCRETE SIDEWALK
19. EXISTING SIDEWALK
20. SAW CUT PIPE BOLLARDS ADJACENT TO OPENINGS IN TENANT WALL FLUSH WITH TOP OF SLAB. TYPICAL 5 BOLLARDS
21. EXIT/EMERGENCY LIGHT FIXTURE
22. 6" STUDS BEHIND TOILET AND LAVATORY
23. INDICATES LOAD BEARING WALL 18 GAUGE STUDS @ 16" O.C. WITH LOAD BEARING PLATE, CONTINUOUS
24. ARMSTRONG 2904 SHASTA, WHITE, WITH 1/2" GRID 2X2 LAY-IN CEILING TILE 9'-4" A.F.F., TYPICAL ALL ROOMS
25. 800S162-43 "C" LIGHT GAUGE FRAMING @ 4'-0" O.C. EXCEPT WHERE NOTED OTHERWISE. SOLID BLOCKING AT MID-SPAN OF JOIST, TYPICAL ALL JOISTS.
26. PERPENDICULAR BRIDGING @ 4'-0" ON TOP FLANGE, 087F125-33 FURRING CHANNEL
27. 3/4" PLYWOOD DECK ON 800S162-43 "C" LIGHT GAUGE JOISTS @ 1'-4" O.C., FOR HVAC EQUIPMENT AND WATER HEATER.
28. CONTINUOUS 8" TRACK CLOSURE AT PERIMETER OF CEILING FRAMING TO CLOSE END OF "C" JOISTS.
29. 6" HIGH VINYL DECAL TO BE APPLIED TO TRACK CLOSURE SHALL READ: "NO STORAGE ABOVE" TWO PLACES ALONG PERIMETER.
30. A.D.A. CLEAR FLOOR AREA AT FIXTURES SEE DRAWING A3 FOR MINIMUM A.D.A. DIMENSIONS AND FIXTURE PLACEMENT.